

SETTING UP HP REMOTE PRINTERS

12/21/2001

From the prompt type...

scoadmin

Tab to the option	printers	hit the enter key
Arrow to	printer manager	hit the enter key
Tab to the remote printer laser1		tab back to printer

Delete the printer laser1.
Arrow to host and enter, exit, & arrow up to HP Network
Arrow down to Printer Manager and enter:
Choose # 6 "Add spooler printer" and enter
Enter the lp spooler name – e.g. laser5
Choose the default name e.g. laser5
Enter the model script - use {standard2} [hit * for choices]
Hit enter on spooler class
Is this the default printer? [y-n]
Ready to shutdown the spooler [y-n-default=y] yes
The printer is added to the spooler - ok to continue [yes]
Pick #4 to ping the printer
Type in the printer name and enter - you will get a response back
You can print a test page by choosing #5
Choose the default text
Next go to sysut and setup a printer in the software

```
Printer Id code.....: Alaser5s*
Description.....: Support txt single side laser*
Location.....: support
[L]ocal/[R]emote/[T]ransparent: R
Printer type ([F7] for query): hplaserj
Forms class.....: plnpaper
Device, file or |Spool|Command.: |lp -dhplaser5a -onofilebreak -ono
Command to execute before open:
Command to execute after close:
```

System printer queue configuration

Type **lp -dlaser1 /.**profile and hit enter to get the response

laser1 is unknown to the lp print server look in the following files and delete the printer from the lpd directory:

- /usr/spool/lpd/laser1**
- /var/spool/lp/admins/lp/printers/laser1**
- /var/spool/lpd/laser1**