

To Configure the TI MicroWriter Printer as a Serial Printer

- | | | |
|---|-------------------------|-------------------|
| 1. Hit the SETUP key until the display reads | Technical Setup | then hit [SELECT] |
| 2. Hit [BACK] until display reads | Pers Prt | then hit [SELECT] |
| 3. Hit [BACK] until display reads | Pers Prt=I | then hit [SELECT] |
| 4. Hit [BACK] until display reads | PP1:Emulator | then hit [SELECT] |
| 5. Hit (BACK) until display reads | Emulator=HP11 | then hit [SELECT] |
| 6. Repeat Steps 1, 2, and 3. | | |
| 7. Hit [BACK] until display reads | PP1:I/O | then hit [SELECT] |
| 8. Hit [BACK] until display reads | I/O:Serial | then hit [SELECT] |
| 9. Repeat Steps 1, 2, and 3. | | |
| 10. Hit (BACK) until display reads | PP1:Orientation | then hit [SELECT] |
| 11. Hit (BACK) until display reads | Orientation=Port | then hit [SELECT] |
| 12. Hit [SETUP] until display reads | 1HP11/Serial | then hit [SELECT] |
| 13. The screen should now have displayed | Online HP11 1 | |

If you have any trouble please call ABCS Hardware Support.