

Digifax Fix after Update

From the prompt type # **swinstall**
Now select the option # **7**

then hit the enter key
digifax **290ojet**

NOTE: The option number may change, however use this option for the fix.

Once you have selected the correct option ... you will be prompted with a choice

1. Select the "I" option when prompted.
2. After the procedure has completed, you will return to the prompt
3. Now go to **Sysut >Printer>Software Printer Maint.**
4. Highlight and select the line for your **Zfax and or Fax**
5. Now edit the Spooler Command line after close (The Bottom Line)
6. Change/ or Edit the following words in that line from **fax_digi** to **faxdigi_jet**

NOW: Do not forget to hit the Insert key, then the F-10 key to SAVE your settings

7. Now, from the prompt type # **faxconfig**
8. Select option # **8**
9. Select choice #**1**
10. Change the number of retries from whatever to "1".
11. Select choice #**2**
12. Change the time between retries to "0" from whatever it currently may be.
13. Select **Q** to quit, and acknowledge that you want to make these changes permanent.
14. "**YES**" to make those changes permanent.
15. Select the #**10** Option to **Stop the Fax Spooler**
16. Select the #**9** Option to **Start the Fax Spooler**

Now log out of any screen that you intend on sending the Fax from. Then log back in and try to send the fax. The fax should work like normal.

6/26/2001 HBM/Charlie
GRN 01/28/01