

Installing Digifax

1. From the prompt Type **# swinstall** then hit the **enter** key
2. Choose **Digifax 290a** then hit the **enter** key
3. Choose **(y)** to reboot after installation then hit the **enter** key
4. Hit **Enter** when prompted
5. When prompted for Dfax fax/1 and fax/2 , **Type N** then hit **enter**
6. When prompted for Jfax- JT fax 9600 **Type N** then hit **enter**
7. When prompted for Bfax- Brooktrout Tretc **Type N** then hit **enter**
8. When prompted for Hpsj- HP Scanjet (Plus) **Type N** then hit **enter**
9. When prompted for Hpsi- HP Scanjet **Type N** then hit **enter**
10. Enter a device name **dfax** to modify, type **(q)** **[enter]**
11. Type **(q)** **[enter]**
12. After confirmed , **[enter]**
13. Type **(q)** **[enter]**
14. After confirmed , **[enter]**
15. Type channel number to modify, type **(1)** **[enter]**
16. Choose **(1)** from menu **[enter]**
17. Type **(efax)** **[enter]**
18. Choose **5** to disable receive, then type **y** and **[enter]**
19. Choose **(18)** from menu **[enter]**
20. Type **(USR-Courier)** **[enter]**
21. Type **(q)** **[enter]**
22. Choose **(13)** from menu **[enter]**
23. Type **(a02)** **[enter]**
24. Type **(q)** **[enter]**
25. Type **(q)** **[enter]**
26. Do you want to make these changes permanent? Type **(y)** **[enter]**
27. After confirmed, **[enter]**
28. Would you like to run /etc/faxconfig right now? Type **(y)** **[enter]**
29. Type **(8)** **[enter]**
30. **Choose 1 and enter choose 1 enter**
31. **Choose 2 and enter choose 1 and enter**
32. Type **(q)** **[enter]**
33. Type **(l)** **[enter]**
34. Now reboot your system. Before use, you will need to configure digifax.